

- **Valve Standard:** Comply with DIN3356.
- **Face to face dimension:** DIN 3202 Series F1.
- **Working Pressure and Temperature**
Working pressure PN16.
Temperature from -10°C to 120°C .
- **Flange Type:**
EN1092-2 PN10/PN16, other flange drillings are available.


Materials Specification

Part Name	Materials	EN Spec.	ASTM Spec.
Body	Cast Iron	EN-JL1040	A126 Class B
Bonnet	Cast Iron	EN-JL1040	A126 Class B
Body Trim	Stainless Steel	BS970 304S15	AISI 304
Disc Trim	Stainless Steel	BS970 304S15	AISI 304
Disc	Cast Iron	EN-JL1040	A126 Class B
Stem	Stainless Steel	17440X20Cr13	AISI 420
Packing	Graphite	Non-asbestos	Non-asbestos
Gasket	Graphite	Non-asbestos	Non-asbestos
Yoke Bushing	Brass	CuZn39Pb3	B16 C36000
Handwheel	Cast Iron	EN-JL1040	A126 Class B

Dimensions(mm)

Size	15	20	25	32	40	50	65	80	100	125	150	200	250	300
L	130	150	160	180	200	230	290	310	350	400	480	600	730	850
D	95	105	115	140	150	165	180	200	220	250	285	340	405	460
H	155	160	180	220	230	250	260	340	377	422	485	568	645	760
C	100	100	100	120	140	140	200	200	240	280	320	360	400	400

